




Setting the Standard

MAGAZINE UNLOADER CE TYPE

Using Pusher, this unit automatically stacks PCB's stacked inside the magazine to the next machine

**Features**

- SMEMA interface
- Dual clamping system for magazine warp prevention
- Easy operation with "Easy S/W"
- Compact design
- LED tower light
- Alarm code display

Options

- 2 Kinds of selectable magazine size
- Space save type
- Touch screen operation
- High speed magazine exchange (19 sec)
- Motorized auto width control system of pusher conveyor
- 5 Rack magazine conveyor
- PCB damage prevention function
- Auto width control
- Customized Manufacturing

| MODEL | TYPE | RAC | Max. PCB (L×W) | Min. PCB (L×W) | Dimension(L×W×H) | Power | AIR(Mpa) | Weight (kg) |
|----------|------|-----|----------------|----------------|------------------|--------|----------|-------------|
| AUD-12CE | S | 3 | 330×250 | 50×50 | 1670×810×1670 | 0.3kVA | 0.5±0.1 | 190 |
| | Y | | 440×330 | 50×65 | 2080×922×1670 | | | 210 |
| | L | | 530×375 | 50×60 | 2550×992×1670 | | | 220 |
| | X | | 530×460 | 50×100 | 2550×1002×1670 | 0.4kVA | | 230 |
| | 2X | | 610×460 | 50×100 | 2820×1062×1670 | | | 260 |